


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>H04M 7/00, 1/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/56159</b> <b>(43) International Publication Date:</b> 10 December 1998 (10.12.98)
<b>(21) International Application Number:</b> PCT/US98/11054 <b>(22) International Filing Date:</b> 29 May 1998 (29.05.98)  <b>(30) Priority Data:</b> 08/868,216      3 June 1997 (03.06.97)      US  <b>(71) Applicant:</b> INFOGEAR TECHNOLOGY CORPORATION [US/US]; Suite 200, 2055 Woodside Road, Redwood City, CA 94061 (US).  <b>(72) Inventor:</b> GIORDANO, Joseph, III; 2324 Hobart Avenue, Southwest, Seattle, WA 98116 (US).  <b>(74) Agents:</b> GLENN, Michael, A. et al.; Law Offices of Michael A. Glenn, P.O. Box 7831, Menlo Park, CA 94026 (US).		<b>(81) Designated States:</b> AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, GW, HU, ID, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>
<b>(54) Title:</b> METHOD AND APPARATUS FOR ICONIFYING AND AUTOMATICALLY DIALING TELEPHONE NUMBERS WHICH APPEAR ON A WEB PAGE		
<b>(57) Abstract</b> <p>A method and apparatus are provided for recognizing and accessing telephone numbers from a Web page. In the preferred embodiment of the invention, an HTML code of an accessed Web page is parsed and converted. A parsing algorithm applied to the text in the HTML document pattern-recognizes telephone numbers. Coding is added to iconify the recognized telephone numbers. The user's Internet-capable telephone displays the iconified telephone numbers. All previously-active links and graphical displays supported by the Internet-capable telephone are maintained in this display. To call a phone number, the user selects the icon, and the Internet-capable phone determines how to initiate the call. For a two-line phone, the Internet-capable telephone initiates a telephone call to the selected number. For a one-line phone, the Internet-capable telephone determines whether the line is available for a call. If the line is not currently being used, the Internet-capable telephone initiates a voice call to the selected number. However, if the user is connected to the Web, the Internet-capable telephone optionally transparently disconnects from the Internet and initiates a voice call to the selected telephone number. At the conclusion of the telephone call, the Internet-capable telephone optionally transparently re-connects to the Web.</p>		



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

# METHOD AND APPARATUS FOR ICONIFYING AND AUTOMATICALLY DIALING TELEPHONE NUMBERS WHICH APPEAR ON A WEB PAGE

5

## BACKGROUND OF THE INVENTION

### TECHNICAL FIELD

10 The invention relates to electronic communication systems. More particularly,  
the invention relates to a system for recognizing and accessing telephone numbers from  
databases distributed over an electronic network.

### DESCRIPTION OF THE PRIOR ART

15 Electronic networks are increasingly being used to store and distribute a variety  
of data. Examples of such electronic networks include the Internet, and intranet  
systems. For example, a World Wide Web (Web) page may include text, graphical  
displays, video displays, animation, and sounds.

20 The Web is usually accessed via telephone lines by a modem-connected  
computer. However, the Web may also be accessed through other devices, including  
personal data assistants, fax machines, and Internet-capable telephones. One telephone  
that provides Web access is described in M. Valentaten, B. Moeschen, Y. Friedman,  
Y.-T. Sidi, Z. Blkowsky, Z. Peleg, *Multi-Mode Home Terminal System that Utilizes a  
Single Embedded General Purpose/DSP Processor and a Single Random Access*  
25 *Memory*, U.S. Patent No. 5,259,940 (October 5, 1993).

A Web page is encoded in Hypertext Markup Language (HTML). An HTML  
document is a plain-text (ASCII) file that uses tags to denote the various elements in the  
document. An element may include an attribute, which is additional information that is  
included between tags.

30 HTML can be used to link text and/or images, such as icons, to another  
document or section of a document. The user activates a link by clicking on it, and the  
linked database is directly accessed. Links are used to access related information, or to  
contact a person or entity. However, information on a Web page must have the  
requisite HTML tags to be an active link.

35 Web pages often contain additional information such as telephone numbers.  
These phone numbers appear as informational numbers, for example, for customer

service, marketing materials, further information, or for advertising. With the expansion of the Web, Web pages that specialize in providing phone numbers are being created. Such Web pages include directory services, white pages, and yellow pages.

5 However, these phone numbers are provided on the Web as text. HTML cannot be used to dial a telephone number over the Internet. Rather, the user must first search the text to locate a phone number. This search may be by visual inspection or by using a search engine to find a particular reference and its associated phone number. To access a number, the user must manually dial the number, or manually input the number into an automatic dialing program.

10 Furthermore, access to the Web is typically via a telephone line. If the user has only one telephone line, the user must disconnect from the Web before the phone number can be dialed. The prior art process for obtaining and calling a phone number listed on the Web is neither time nor cost effective, especially in a business environment.

15 It would therefore be an advantage to provide a system for recognizing telephone numbers from the World Wide Web. It would be a further advantage if such system if the system iconified telephone numbers to permit automatic dialing of a selected number. It would be yet another advantage if such system organized such telephone numbers to facilitate locating a desired number.

20

### SUMMARY OF THE INVENTION

The invention provides a method and apparatus for recognizing and accessing telephone numbers that are contained within a Web page. The telephone numbers are iconified to permit automatic dialing of a selected number.

25 The preferred embodiment of the invention is adapted for use with a Web telephone. However, alternative embodiments of the invention are adapted for use with any Internet access device. In the preferred embodiment of the invention, either the server that controls Internet access or a client parses the HTML code of an accessed Web page. A parsing algorithm applied to the text in the HTML document pattern-recognizes telephone numbers having a standard format, such as United States numbers or international phone numbers.

30 Coding is added to iconify recognized telephone numbers. The invention may be configured to iconify all pattern-recognized telephone numbers, or to iconify only those numbers meeting specific criteria. An iconified telephone number is identified on the Internet-capable telephone screen by means including a button surrounding the

number, font appearance, underlining, or highlighting. Iconified telephone numbers may be either automatically or manually stored in an address book for later use.

To call a phone number, the user selects the icon, for example, by clicking on it. The Internet-capable phone determines how to initiate the call. If the user has a two-line  
5 phone, the Internet-capable telephone initiates a telephone call to the selected number.

If the user has a one-line phone, the Internet-capable telephone determines whether the line is available for a call. If the line isn't currently being used, the Internet-capable telephone initiates a voice call to the selected number. However, if the user is connected to the Web, the Internet-capable telephone automatically disconnects  
10 from the Internet and initiates a voice call to the selected telephone number. At the conclusion of the telephone call, the Internet-capable telephone may or may not automatically re-connect to the Web.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

15

Fig. 1 is a flow chart of a method for recognizing and accessing telephone numbers according to the preferred embodiment of the invention;

Fig. 2 is a flow chart of an algorithm for recognizing telephone numbers according to the invention; and

20 Fig. 3 is a flow chart of a method for accessing telephone numbers according to the invention.

### **DETAILED DESCRIPTION OF THE INVENTION**

25 The invention provides a method and system for recognizing telephone numbers from a Web page. The telephone numbers are iconified to permit automatic dialing of a selected number.

Fig. 1 is a flow chart of a method for recognizing and accessing telephone numbers, according to the preferred embodiment of the invention. The preferred  
30 embodiment of the invention is adapted for use with the Web technique described above. (See U.S. Patent No. 5,250,940.) However, alternative embodiments of the invention are adapted for use with any Internet access device.

The server that controls Internet access for the I-Phone parses the HTML code of an accessed Web page (100). While parsing the HTML, the server examines the text  
35 in the HTML document. It should be appreciated that parsing may just as readily be performed on the Client instead of the server. Thus, the following discussion is provided for purposes of example and not as a limitation on the scope of the invention.

An algorithm is applied to this text to pattern-recognize telephone numbers (105). The algorithm is readily modified to recognize any telephone numbers having a standard format, such as United States numbers or international phone numbers.

5 The layout is then rendered in a displayable form (110). In the preferred embodiment of the invention, the server (or the Client) converts the HTML layout to an equivalent of the HTML layout (115). Alternative embodiments of the invention do not convert the HTML layout, or convert the HTML to different browser formats.

10 Where the parsing is performed by the server, the HTML page can be converted into different formats prior to being sent to clients, depending on the client's particular requirements. For example, an HTML page can be converted into formats accessible by a Web telephone, a cellular phone, or a personal digital assistant having a wireless phone. The files are sent to the user's Internet-capable telephone and the Web page is displayed on the telephone's screen (120). All previously-active links and graphical displays supported by the Internet-capable telephone are maintained in this display.

15 As a part of the HTML conversion, coding is added to iconify recognized telephone numbers (125). The invention may be configured to iconify all pattern-recognized telephone numbers, or to iconify only those numbers meeting specific criteria. In this case, a restrictor is used to direct the pattern-recognition software to only recognize or to ignore certain area codes, not to iconify certain foreign-country  
20 telephone numbers, or to iconify only telephone numbers associated with specific text headings such as "Customer Support." In such case the number still appears on the screen display, but is not iconified.

In the preferred embodiment of the invention, an iconified telephone number is identified on the Internet-capable telephone screen by a button surrounding the number.  
25 However, in alternative embodiments, the telephone number may be identified by different means, such as font appearance, underlining, or highlighting.

Fig. 2 is a flow chart of an algorithm for recognizing telephone numbers, according to the invention. A set of Picture Formats are developed for the patterns of phone numbers. While the software program is reading the HTML document, it reads  
30 the text of every character that it comes across and checks to see if the text is a number (200). If the character is non-numeric (225), HTML parsing continues. However, the identification of a number (205) triggers the pattern-recognition algorithm (210). The pattern-recognition algorithm sequentially checks the characters following the identified number to determine if they also are numbers. A series of consecutive numbers is  
35 cached (215) and then compared to the Picture Formats (220). A matching format indicates a telephone number.

Telephone numbers can include text, such as hyphens or parentheses, or spaces interspersed with numbers. The patterns in the Picture Formats are therefore defined by those text characters that can be before and in between numbers. Because some text characters void the pattern, the algorithm should take this into account (230). Thus, the algorithm can distinguish, for example, among parentheses surrounding an area code, parentheses surrounding a sentence, and a serial number containing both numbers and text characters.

The patterns in the Picture Formats are also defined by the length of the number string. For example, U.S. area codes are usually three digits, and prefixes are usually three digits, followed by four final digits.

The following is an example of an algorithm that supports U.S. phone numbers. The algorithm looks for the following patterns:

```
'xxx*xxxx';
'x*xxx*xxxx';
'xxx**xxx*xxxx'; and
'x**xxx**xxx*xxxx';
```

where x represents a numeric digit, \* represents one character, and \*\* represents either one or two characters, all of which can only be equal to "-", ") ", ".", or " ". There is a first character case that is omitted which is a "+" or a "(" .

Fig. 3 is a flow chart of a method for accessing telephone numbers, according to the invention. To call a phone number, the user selects the icon by clicking on it, or by another suitable selection method (300). The Internet-capable phone makes the determination of how to initiate the call (305). If the user has a two-line phone, the Internet-capable telephone initiates a telephone call to the selected number (335).

If the user has a one-line phone (315), the Internet-capable telephone first determines whether the line is available for a call. If the line is not currently being used for another telephone call or to connect to the Internet (325), the Internet-capable telephone initiates a voice call to the selected number (335). However, if the user is connected to the Web (320), the Internet-capable telephone automatically, and transparently, disconnects from the Internet session (330) and initiates a voice call to the selected telephone number.

The Internet-capable telephone recognizes the conclusion of the call and terminates the telephone call session (340). The Internet-capable telephone may then automatically, and transparently, re-connect to the Web (345). If desired, this feature may be a user-determined preference. In alternative embodiments of the invention, the Internet-capable telephone may be configured to re-connect to the Web only when directed to do so by the user. The Internet-capable telephone is thus seamlessly integrated with the Web.

In one embodiment of the invention, the pattern-recognition software is configured to recognize identification. For example, telephone numbers directly following headings such as Technical Support or Sales are recognized and iconified. In one embodiment of the invention, the pattern-recognition algorithm is configured for use with an Internet Telephone directory. The user can then look up a telephone number in such a directory and directly dial the retrieved numbers from the Internet-capable telephone display screen.

In an alternative embodiment of the invention, iconified telephone numbers are stored in an address book for later use. For example, HTML tags in an Internet telephone directory that identify a record, e.g. including name and address, that can be added to an address book are recognized. These records can then be either automatically or manually added to the user's address book. In a manual implementation, the Internet-capable telephone displays a button or other type of selection means that the user can select to store a record, including such information as name and address.

Although the invention is described herein with reference to the preferred embodiment, one skilled in the art will readily appreciate that other applications may be substituted for those set forth herein without departing from the spirit and scope of the present invention.

For example, in the preferred embodiment of the invention, the translation from HTML is performed by the server. However, in alternative embodiments, the translation is performed by the Internet-capable telephone, or by a computer networked to the Internet-capable telephone. Further, such conversion may be an HTML-to-HTML conversion, for example as provided by a plug-in that operates in a connection with a conventional Web browser, such as Navigator, manufactured by Netscape Communications Corporation of Mountain View, California. Further, pattern recognition may be performed by the Client.

Accordingly, the invention should only be limited by the Claims included below.



### CLAIMS

1. A method for identifying telephone numbers within an electronic document  
5 during a communications session, comprising the steps of:  
parsing said electronic document;  
recognizing a telephone number contained within an electronic document; and  
converting said telephone number to an iconic representation.
- 10 2. The method of Claim 1, wherein said recognizing step comprised the steps of:  
transparently disconnecting from said session upon selection of said iconified  
telephone number and calling said telephone number.
- 15 3. The method of Claim 2, further comprising the steps of:  
recognizing the termination of said telephone call; and  
transparently re-connecting to said session.
- 20 4. The method of Claim 1, said parsing step comprising the step of:  
applying a parsing algorithm to said electronic document to pattern-recognize a  
telephone number contained therein.
- 25 5. The method of Claim 1, further comprising the step of:  
transmitting or displaying said electronic document with said iconified telephone  
number to a complementary device.
6. The method of Claim 5, wherein said device is an Internet-capable telephone.
- 30 7. The method of Claim 1, further comprising the steps of:  
converting an HTML code representation of a Web page; and  
adding a representation that iconifies said recognized telephone number.
8. The method of Claim 7, wherein said HTML code representation is translated to  
another format at either a server or a client device.
- 35 9. The method of Claim 1, wherein said iconified telephone number is identified  
by one of a button surrounding the number, font appearance, underlining, or  
highlighting.

10. The method of Claim 1, wherein all recognized telephone numbers are iconified.
11. The method of Claim 1, wherein telephone numbers meeting specific criteria are  
5 iconified.
12. The method of Claim 4, said parsing algorithm comprising the steps of:  
developing a set of Picture Formats for the patterns of phone numbers;  
reading an accessed electronic document;  
10 checking every character in the text of said electronic document to determine if it  
is a numeric character;  
applying a pattern-recognition algorithm to sequentially check a character  
following an identified number to determine if said character is any of numeric or an  
interspersed text or punctuation character;  
15 caching a series of consecutive numbers; and  
comparing said caches series to said Picture Formats;  
wherein a matching format indicates a telephone number.
13. The method of Claim 2, wherein said step of transparently disconnecting from  
20 said session upon selection of said iconified telephone number and calling said  
telephone number comprises the steps of:  
selecting an iconified telephone number in a display of an access device;  
said access device initiating a telephone call to said selected number if a  
telephone line or sufficient bandwidth is available;  
25 said access device transparently disconnecting from said session if a telephone  
line is not available, and thereupon initiating a telephone call to said selected telephone  
number;  
said access device recognizing the termination of said telephone call; and  
said access device optionally transparently re-connecting to said session.  
30
14. The method of Claim 1, further comprising the step of:  
automatically storing said iconified telephone number in an address book.
15. A method for recognizing and accessing telephone numbers from a Web page,  
35 comprising the steps of:  
parsing the HTML code of a Web page accessed during an Internet session;

applying a parsing algorithm to the text of said Web page to pattern-recognize a telephone number contained therein;

converting said HTML code to a representation of said Web page;

5 adding to said representation coding to iconify said recognized telephone number;

transmitting said Web page with said iconified telephone number to an access device for display;

transparently disconnecting from said Internet session upon selection of said iconified telephone number and calling said telephone number;

10 recognizing the termination of said telephone call; and  
optionally transparently re-connecting to the Internet.

16. The method of Claim 14, wherein said parsing algorithm comprises the steps of:  
developing a set of Picture Formats for the patterns of phone numbers;

15 reading an accessed HTML document using a software program on a server;  
checking every character in the text of said HTML document to determine if it is a numeric character;

using a pattern-recognition algorithm to sequentially check a character following an identified number to determine if said character is any of numeric or an interspersed text or punctuation character;

20 caching a series of consecutive numbers; and  
comparing said caches series to said Picture Formats;  
wherein a matching format indicates a telephone number.

25 17. The method of Claim 15, wherein said iconified telephone number is identified by one of a button surrounding the number, font appearance, underlining, or highlighting.

30 18. The method of Claim 15, wherein all recognized telephone numbers are iconified.

19. The method of Claim 15, wherein telephone numbers meeting specific criteria are iconified.

35 20. The method of Claim 15, further comprising the step of automatically storing said iconified telephone number and related information in an address book.

21. A system for recognizing and accessing telephone numbers from a Web page, comprising:
- a module for parsing the HTML code of a Web page accessed during an Internet session; and
  - 5 a parsing algorithm used by said module to pattern-recognize a telephone number contained in the text of said Web page.
22. The system of Claim 21, further comprising:
- a conversion module used to convert said parsed HTML code to a representation
  - 10 of said Web page; and
  - an iconifying module used by said conversion module to add to said representation coding to iconify said recognized telephone number.
23. An access appliance, comprising:
- 15 a Web telephone for receiving and displaying a Web page having an iconified telephone number; and
  - a software module used by said Web telephone to transparently disconnect from an Internet session upon selection of said iconified telephone number and to call said telephone number;
  - 20 wherein said Web telephone software module recognizes the termination of said telephone call and optionally transparently re-connects to the Internet.

1/3




FIG. 1

2/3




FIG. 2

3/3




FIG. 3

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/11054

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M7/00 H04M1/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	PANDIT ET AL: "THE SELECTION RECOGNITION AGENT: INSTANT ACCESS TO RELEVANT INFORMATION AND OPERATIONS" INTERNATIONAL CONFERENCE ON INTELLIGENT USER INTERFACE, ORLANDO (US), 6 January 1997, pages 47-52, XP000731429 see the whole document ---	1-4, 7, 9, 13, 15, 17, 21-23
Y	US 5 483 352 A (FUKUYAMA ET AL) 9 January 1996  see column 4, line 36 - column 10, line 17; figures 4-12 --- -/--	1-4, 7, 9, 13, 15, 17, 21-23

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 October 1998

Date of mailing of the international search report

12/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Delangue, P



# INTERNATIONAL SEARCH REPORT

Inte. national Application No

PCT/US 98/11054

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 13382 A (NORTHERN TELECOM LTD) 10 April 1997  see page 6, line 1 - page 14, line 15; figures 1-9  ---	1-4,7,9, 13,15, 17,21-23
A	WO 97 13352 A (NORTHERN TELECOM LTD) 10 April 1997  see page 10, line 1 - page 18, line 20; figures 1,2  ---	1-4,7,9, 13,15, 17,21-23
A	LOW C: "THE INTERNET TELEPHONY RED HERRING" HP LABORATORIES TECHNICAL REPORT, 15 May 1996, pages 1-15, XP002043901 see page 7 - page 12  ---	1-4,9, 13,15, 17,21-23
A	DE 196 44 210 A (MITEL CORP) 30 April 1997  see column 2, line 32 - line 44 see column 2, line 58 - column 7, line 9; figures 1-5  ---	1,2,7,9, 21-23
A	US 4 995 074 A (GOLDMAN ET AL) 19 February 1991 see abstract  ---	1-3,13, 15,23
E	US 5 764 736 A (SHACHAR ET AL) 9 June 1998  see column 7, line 38 - column 14, line 60; figures 1-4  -----	1-4,7,9, 13,15, 17,21-23

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/11054

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5483352 A	09-01-1996	JP 2756392 B JP 6077995 A	25-05-1998 18-03-1994
WO 9713382 A	10-04-1997	AU 6982596 A EP 0852884 A	28-04-1997 15-07-1998
WO 9713352 A	10-04-1997	AU 694682 B AU 6729596 A EP 0852872 A	23-07-1998 28-04-1997 15-07-1998
DE 19644210 A	30-04-1997	CA 2161506 A GB 2306853 A SE 9603855 A	27-04-1997 07-05-1997 27-04-1997
US 4995074 A	19-02-1991	NONE	
US 5764736 A	09-06-1998	NONE	